

## Hinged Fibre Splice Enclosure

V.3.1

### Features / Benefits


- ▶ **Opens via left hand hinge**
- ▶ **Multi cable entry points**
- ▶ **Integrated Pressure valve**
- ▶ **Integrated Earth Point**
- ▶ **Holds up to 60 single Fibres**
- ▶ **Integrated fibre management**
- ▶ **Mechanically Sealed (compression)**
- ▶ **Multi Functional Splicing Options**
- ▶ **Includes All Splice Protection**
- ▶ **Includes Wall Mounting Bracket and Fixings**
- ▶ **Can Be Pole Mounted (Optional Extra)**
- ▶ **Can Be Aerial Mounted (Optional Extra)**

### Technical Specification

PRODUCT SPECIFICATION	
Maximum Single Fibre Count	60
Maximum Fibres Per Tray	12
Maximum Number Of Trays	5
Number Of Cable Entry Points	3
Suitable For Cable Diameters	8mm to 15mm Ø
Number of Pigtail Outlets	4
Suitable For Pigtail Diameter	2mm Ø
Number of Uncut Cable Entry	1
Suitable For Uncut Cable Diameter	8mm to 15mm Ø
Number of Test outlets	1
Suitable For Test Cable Diameter	6mm Ø
Sealing Rating	IP68
Sealing Method For All Entry And Exit	Mechanical (compression)
Height	300mm
Width	220mm
Depth	100mm
Weight	2.4kgs to 2.7kgs
Colour	Black
Material	ABS
RoHS Compliant	Yes
Optimal Operating Temperature	-40 °C to +65 °C

### Ordering Information

DESCRIPTION	PART NO.
Hinged Fibre Splice Enclosure 12 splice	<b>DOME05</b>
Hinged Fibre Splice Enclosure 24 splice	<b>DOME06</b>
Hinged Fibre Splice Enclosure 36 splice	<b>DOME07</b>
Hinged Fibre Splice Enclosure 48 splice	<b>DOME08</b>
Hinged Fibre Splice Enclosure 60 splice	<b>DOME09</b>
Optional Extra	PART NO.
Pole mounting Kit	<b>POLEKIT</b>
Aerial Mounting Kit	<b>AERIALKIT</b>



+44 (0) 870 127 3330



+44 (0) 870 127 3331



sales@fibrefab.com



www.fibrefab.com