

Termination Boxes

Compact Termination Box

NEW



The FibreFab compact termination box is designed for use in residential and business applications for the termination of up to four fibres. The wall box enables the installation of either a single Blown Tube cable using up to a 4 fibre blown unit or two 2 fibre ruggedised cables to be spliced to four SC pigtails (PC or APC), which connect to adapters at the base of the unit.

The unit can be quickly installed within an office, house or communication room environment.

Features

- ▶ Ergonomic design.
- ▶ Ability to allow cables to enter from rear or bottom of the unit.
- ▶ All fibres are positively managed to maintain a 30mm minimum bend radius.
- ▶ Optional Removable rear entry cable management.
- ▶ Flip tray to allow access to connectorised tails and cable entry.
- ▶ Removable cover for easy access.
- ▶ Tamperproof cover security screws available as an option.
- ▶ Unit manufactured from fire resistant UL94-V0 rated material.
- ▶ Patchcords exit unit on bottom face and are protected by two protection covers.
- ▶ Standard colour white. Other colours available on request.

Specification

Number of splice trays:	1
Maximum Fibre Capacity:	4 Fibres
Maximum Cable Diameter (mm):	10
Maximum no. of customer feeds:	4 Patchcords
Required space envelope (mm):	(l) 80 x (w) 120 x (d) 25
Operating temperature:	-20oC to + 50oC (5 to 95% RH)
Material:	
• Cap:	FR High Impact Polystyrene
• Base:	FR High Impact Polystyrene
• Splitter trays:	FR High Impact Polystyrene
Testing:	
• Dry heat:	BS EN 60068-2-2 Test Bb
• Damp heat:	IEC 60068-2-3: 1969
• Change of temperature:	IEC 60068-2-14: 1984
• Vibration:	IEC 60068-2-6: 1995
• Shock:	IEC 60068-2-27: 1987
Packing Dimensions (mm):	(w) 230 x (h) 160 x (d) 60
Packed Weight (kg):	0.55
Net weight (kg):	0.50



Compact Termination Box	
Description	Product Code
Compact termination box	CSB06