

## Category 3 Voice Patch panel

### Description

FibreFab's Category 3 high density voice patch panels offer a cost effective method for integrating voice circuits into standard structured cabling systems. Available in both 25 and 50 ports on a 1U 19" footprint, ideal for maximising rack space.

### Features

- ▶ 19" rack mountable
- ▶ Accepts 24-26 AWG
- ▶ Supplied with fixings and earthing wire
- ▶ IDC punch down
- ▶ 25 or 50 RJ45 ports on 1U footprint
- ▶ Integral cable management and grounding clamps

### Applications

- ▶ Voice integration into standard structured cabling systems

### Conformance

- ▶ Category 3
- ▶ ISO/IEC 11801 : 2002
- ▶ ANSI/EIA/TIA 568B.2.1 : 2002
- ▶ UL approved

### Technical Specification

MECHANICAL	VALUE
Housing Material	PBT + 15% GF UL94V-0
Panel Frame	Carbon Steel, Powder Coating
Contact Material	PC UL94V-0 Contact: Phosphor Bronze + Nickel Plating
RJ45 Jack Life	Min 750 Insertions
IDC Life	Min 200 Terminations

### Ordering Information

DESCRIPTION	PART NO
Optronic Category 3 1U 25 port voice patch panel Black - UL approved	<b>CAT3+LSA25</b>
Optronic Category 3 1U 50 port voice patch panel Black - UL approved	<b>CAT3+LSA50</b>

